



**CASTELMONTE**  
*Le grandi stufe italiane*

## Marilyn Pellet

<b>Maximum thermal capacity</b>	<b>13 kW</b>
<b>Dimensions (mm.)</b>	<b>565 x 520 x 1160</b>
<b>Net weight</b>	<b>163 kg</b>
<b>Pellet tank capacity</b>	<b>20 kg</b>
<b>Pellet consumption (min.-max.)</b>	<b>0,9 – 2,6 kg/h</b>
<b>Run time (min. – max.)</b>	<b>7,7 – 30,7 h</b>
<b>Electric power at the ignition</b>	<b>300 W</b>
<b>Electric power at the operation</b>	<b>100 W</b>
<b>Fuel</b>	<b>Pellet ( diam. 6 mm.)</b>
<b>Exhaust pipe</b>	<b>diam.80 mm.</b>
<b>Control and setting</b>	<b>Radiocontrol</b>
<b>Automatic combustion control</b>	<b>Eco Control</b>



**CASTELMONTE srl**  
Via Vicinale di Parabiago 14  
20014 Nerviano (MI) ITALY

**Technical specifications as per standard EN 14785:2006**

<b>Model:</b> Marilyn Pellet	
Thermal capacity	nominal: 11,8 KW minimum: 5 KW
CO measured (at 13% of Oxigen)	nominal: 0,014% minimum: 0,047%
Efficiency	nominal: 86,4% minimum: 87,3%
Average fumes temperature	nominal: 238 °C minimum: 134 °C
Maximum electric Power Absorption	300 W
Nominal Voltage and Frequency	230V – 50 Hz
Minimum safety distance from inflammable materials:	side: 20 cm. rear: 20 cm.
<b>This pellet stove is suitable for continuous operation</b>	
<b>Only use recommended fuel!</b>	
<b>Read and follow the operating instructions!</b>	
<b>This pellet stove cannot be used on a shared flue</b>	

