



# CASTELMONTE

*Le grandi stufe italiane*

## Marilyn Pellet KANALISIERBAR

Maximum thermal capacity	13 KW
Dimensions (mm.)	565x620x1160
Net weight	178 Kg.
Pellet tank capacity	20 Kg.
Pellet consumption (min. – max)	0,9-2,6 Kg/h
Electric power at the ignition	300 W
Electric power at the operation	100 W
Fuel	pellet diam. 6 mm.
Exhaust pipe	diam. 80 mm.
Duct pipe	diam. 100 mm.
Duct maximum length	6 mt.
Control and setting	IR control

 13		CASTELMONTE srl Via Vicinale di Parabiago 14 20014 Nerviano (MI) ITALY
Technical specifications as per standard EN 14786:2008		
Model: Marilyn Pellet Canalizzata		
Thermal capacity	nominal: 11,8 kW minimum: 5 kW	
CO measured (at 13% of Oxygen)	nominal: 0,014% minimum: 0,047%	
Efficiency	nominal: 86,4% minimum: 87,3%	
Average fumes temperature	nominal: 238 °C minimum: 134 °C	
Maximum electric Power Absorption	300 W	
Nominal Voltage and Frequency	230V – 50 Hz	
Minimum safety distance from Inflammable materials:	side: 20 cm. rear: 20 cm.	
This pellet stove is suitable for continuous operation		
Only use recommended fuel!		
Read and follow the operating instructions!		
This pellet stove cannot be used on a shared flue		

